

# NF3000C-SVF Series (RoHS认证产品)

三相三线式 500VAC

书状, 宽带高衰减型



50A产品 外观



Type Approved  
Safety  
Regular Production  
Surveillance

www.tuv.com  
ID 2000000000

UL1283/CSA C22.2 No8(C-UL) (file No.E102708)

EN60939-2 (file No.R50147282)

SCCR对应品

- 与断路器组合取得
- 若为Listed认证品, 可使用任何厂家的断路器




## 用途

工作机械、通用变频器以及AC伺服等

## 规格


Parts No.	Rated Current	SCCR value	Weight	
NF3010C-SVF	10A	10kA	0.6Kg	fig1
NF3020C-SVF	20A		0.7Kg	
NF3030C-SVF	30A		0.7Kg	
NF3040C-SVF	40A	14kA	1.1Kg	fig2
NF3050C-SVF	50A	22kA	1.1Kg	
NF3060C-SVF	60A		1.1Kg	fig3
NF3080C-SVF	80A		2.6Kg	
NF3100C-SVF	100A		2.7Kg	
NF3150C-SVF	150A	30kA	4.3Kg	fig4
NF3200C-SVF	200A	42kA	6.9Kg	fig5
NF3250C-SVF	250A		8.1Kg	
NF3300C-SVF	300A		8.1Kg	
Rated Voltage	530VAC max			
Leakage Current	10-150A: 2.5mA/200-300A: 10mA max 400VAC 50Hz			
Ambient temp.	-20 up to 50 Deg.C			

fig.1 (10-30A)



No	Part name	Note
1	Input terminal	M4
2	Case	PBT
3	Name plate	
4	Output terminal	M4
5	Earth terminal	M4

**fig.2 (40-60A)**



**fig.3 (80A, 100A)**




fig.4 (150A)






fig.5 (200-300A)



代表特性 (50A)



电路图

